



CHANGE-KIT-08

Access WARRIOR 450

ENGINE OIL CHANGE KIT

Instructions:

- Place the ATV on a level surface and secure it against rolling away.
- Select Neutral, start the engine, let it warm up on idle for cca 5 minutes and turn the engine off.
- Place a suitable container / pan that holds at least 3.0 liters under the engine.
- Loosen the drain plug at the bottom of the engine (17mm Hex Screw). Do not drop the screw into the pan.
- Carefully drain warm oil and allow it to drain completely. **WARNING: OIL CAN BE VERY HOT!**
- Loosen the oil filter cartridge with the oil filter wrench. The oil filter is located in front of the engine.
- Allow the oil to drain from the oil filter cartridge. Wipe away any spilled oil.
- Lubricate the rubber gasket of a new oil filter cartridge with clean engine oil.
- Install new oil filter. Screw the cartridge on the engine hand-tight. Do not over tighten the filter.
- Screw the oil drain plug back into the engine. (Tightening torque: 30 Nm).
- Unscrew and remove the oil dip stick - new oil filling point.
- Using a funnel, carefully pour about 1,2 liters of 10W-40 oil into the engine. Avoid overfilling the funnel.
- Screw the dip stick back into the engine and wipe off any oil residues.
- Start the engine for cca 20 seconds, check for oil leaks.
- Stop the engine, wait for about 10 seconds, unscrew the oil dip stick and check the oil level.
- Put the dip stick on top of the threads (do not screw it in), pull the dip stick out and check the oil level.
- Top up the remaining 0,4 litres of oil.
- If the oil level reaches the upper mark on the dip stick, reinstall the dip stick.
- In general, you should use about 1,6 l liters of oil when changing.
- Screw the dip stick back into the engine, again start the engine for cca 20 seconds, then stop the engine, wait for about 10 seconds and check the oil level with the dip stick.
- Oil level should be between the upper and lower marks.
- If not, add the oil to the max level by repeating the steps above.
- Clean spilled oil, start the engine and check for oil leaks.
- Congratulations: you have successfully replaced your oil and oil filter!
- Dispose of the used oil ecologically - take your used oil and oil filter in for recycling.

CHANGE-KIT-08 includes:

- **1x Oil Filter**, Part: 15290-E12-200
- **3x 1L MAXIMA ATV PREMIUM 10W40 4T Oil**, Part: 33901 (Engine oil)
- **Instruction sheet**



OFFICIAL DISTRIBUTOR:

ASP Group Distributing, Staroplzenecka 290, 326 00, Letkov, CZ, tel: +420 378 21 21 21, info@aspgroup.cz, www.aspgroup.eu